

45. SAILS

- a) The sails shall be made of woven cloth.
- b) Headboard in the mainsail, excluding bolt ropes shall not exceed 115 mm measured square to the mast. No headboard is allowed in the jib.
- c) Only the jib may have a transparent window.
- d) The sails shall be measured as per the ISAF sail measurement instructions.
- e) Mylar may not be used in the cloth of which the sails are made.

Replace 45 a) with:

Sails shall be constructed from Polyester materials and classified as *Soft Sails* made from a *Single Ply* which is either a *Woven Ply* or a *Laminated Ply* or both (Words in italics defined in the ISAF ERS.)

Change 45 d) to read:

The sails shall be measured in accordance with the ISAF Guide to Sail Measurement.

Delete 45 e) above

46. Mainsail : The mainsail shall conform to the following measurements :

- | | | |
|---|-------|------------------|
| a) half height width excluding luff bolt rope | (max) | 1485mm |
| b) leech | (max) | 3810mm |
| c) Battens - 3 in number, approximately equally spaced along the leech. - Length of batten | (max) | 610mm |
| d) Dabchick insignia and numbers shall be not less than | | 200 x 140 x 30mm |
| e) Conventional and loose footed mainsails are permitted. For loose footed sails the distance from the head to the midpoint of the foot shall not exceed 3750 mm. | (max) | 3750mm |

Add f) Optional: Top Batten.

The top batten of the battens described in 45 c) above may be replaced by one conforming to the following

- | | | |
|--|-------|--------|
| length from head of sail to top of batten pocket down luff | (min) | 960mm |
| length of top of batten pocket from luff to leech | (max) | 1080mm |

The numbers shall conform to the requirements of the ISAF Racing Rules

47. Jib : The jib shall conform to the following measurements :

- | | | |
|---|-------|------------|
| a) Luff and leech | (max) | 2667mm |
| b) Foot | (max) | 1473mm |
| c) Centre measurement from highest point of sail on the luff to the lowest edge of the sail at the mid point of the foot. | (max) | 2720mm |
| d) Optional window, size | (max) | 3000 sq.cm |
- The window shall be no nearer than 150mm from any sail edge.

48. A single track adjustable fairlead may be fitted on the port and starboard deck. No barber haulers are allowed.

49. Sails and spars used in the first race of a series shall not be changed during the series. In the event of irreparable damage the written permission of the race committee shall be obtained before substitution.